

## DESOI M-Power MB-H

No. 10765

### Description

The handy and compact manual membrane pump DESOI M-Power MB-H is efficient and suitable for quick service on site. The ready-mixed material is sucked directly out of the mixing container.

### Material to be used

- Injection mortar
- Cement paste
- Cement suspension
- Aqueous solution

### Delivery range

suction system, accumulator with manometer  
0 – 25 bar, incl. instruction manual,  
No. 10913: Material hose (Ø 13 mm, 3 m long,  
detachable double nipple R ½"),  
No. 10920: Quick snap (LP ball valve R ½", max.  
40 bar, free passage Ø 9 mm, detachable double  
nipple R ½"),  
No. 21232: LP ball valve R ½" (max. 40 bar, mouth  
piece, detachable double nipple R ½")

### Advantages

- Accumulator with manometer for pressure control and constant material output
- Big material passages - high flow rate
- Easy operation and cleaning



1. Accumulator with manometer

2. Suction system with filter

### Technical data

Working pressure - acc. to compressive force	0 – 20 bar
Delivery rate	150 ml/stroke
Grain size	max. 0.3 mm
Weight	14 kg
L x W x H	60 x 18 x 100 cm

### Accessories

Spare and wear part set DESOI M-Power MB-F/MB-H	No. 10760-EVS
Set of tools DESOI M-Power MB-F/MB-H	10760-WS